

亚 / 克 / 迪 / 智 / 能 改 / 变 / 未 / 来
AKODI CHANGE THE WORLD

AKODiTM
INTELLIGENT LOGISTICS TECHNOLOGY

ISO9001: 2008



CHINA
GUANGDONG
AKODI
INTELLIGENT LOGISTICS TECHNOLOGY
广东亚克迪智能物流科技有限公司 **CO.,LTD**

本公司专业生产、销售“AKODI”系列物流机械设备，为企业提供智能物流解决方案，产品目前主要销往国内外市场。

亚克迪愿景：亚克迪智能，改变未来！有物流，就有亚克迪！

使命：响应“中国制造2025”中“智能制造”的发展方向，打造用户智能物流解决方案，为“中国制造2025”做出贡献！

价值观：海阔天空地想，脚踏实地干。

The company was established in 1989. We have many years of experience in the logistics market. Our vision is to achieve Win-Win situation. We will provide solutions to meet our client's requirements/ market demands. Our priority is safety for all our cost-effective material handling equipment. Our company manufactures one of the best pallet trucks (electric/manual) in the market. We focus on R&D in order to provide products with best quality (ISO, CE) and competitive pricing. Keep your business moving.



ISO9001: 2008



公众号



小程序

智能全电动托盘搬运车 Intelligent Electric Pallet Truck

- ◆ 拉杆式原理货叉：减少货叉磨损，提高爬坡能力。
- ◆ 高配置进口系统和无刷交流电机：电马力大，提高工作效率，稳定可靠。
- ◆ 电子转向：反应灵敏，操控灵活。
- ◆ 手柄紧急反向开关：提高操作人员安全性。
- ◆ 多功能控制手柄：符合人体工程学原理，提供操作舒适度，手柄被释放时自动停机。
- ◆ 吸震防滑站台：舒适稳定。
- ◆ 选配：机械转向。

- ◆ Pull-rod design fork: reduces fork wear, eliminating costly fork repairs.
- ◆ Curtis control system and brushless AC motor: powerful, improved work efficiency, and reliability.
- ◆ Multifunctional handle: ergonomics, comfortable operation, increased work efficiency, break override feature.
- ◆ Shock-absorbing and anti-skid platform: comfortable standing for operation.
- ◆ Optional: mechanical steering.



参数项目Parameters / 型号Model		AKCDH20	AKCDH30
额定载荷 Capacity	Kg	2000	3000
载荷中心 Load center	mm	600	600
转弯半径 Turning radius	mm	1570 (1715)	1570 (1715)
起升高度 Max.lift height	mm	205	205
货叉最低高度 Min. height	mm	82	82
货叉尺寸 Fork size	mm	160x1220	160x1220
货叉外宽 Overall Fork width	mm	550/680	550/680
整车宽度 Overall width	mm	775	775
整车长度 Overall length	mm	1956	1956
整车高度 Overall height	mm	1415	1415
行驶速度(满载/空载) Max. Travelling speed (laden/unladen) controllable	km/h	5.5/5.8	5.5/5.8
驾驶方式 Driving Method		站驾式Stand	站驾式Stand
转向 Steering		电子(Electronic)	电子(Electronic)
蓄电池 Battery	V/Ah	24V / 210 Ah	24V / 270 Ah
充电器 External charger	V/A	DC24V/30A	DC24V/30A
蓄电池充满电工作時間 Working hours once fully charged	h	6 ~ 8	6 ~ 8
自重 Weight	kg	380/420	445/485
电池重量 Battery weight	kg	175	195

经济型全电动托盘搬运车 Economic Electric Pallet Truck



- ◆体积小：转弯半径小，适合在有限空间作业。
 - ◆直流电机驱动系统：损耗少，效率高，性价比高。
 - ◆操作手柄：符合人体工程学原理，操作舒适。
 - ◆德国原装进口方式微动开关：适应多种恶劣环境。
 - ◆龟速开关：精准控制速度。
 - ◆免维护电池和外置充电器：维修简便，充电器散热性能更佳。
-
- ◆ Smaller size: smaller turning radius, suitable for operation in confined space.
 - ◆ DC motor drive system: high efficiency, and cost-effective.
 - ◆ Multifunctional handle: ergonomics, comfortable operation, increased work efficiency.
 - ◆ German import micro switch: adaptable in a variety of harsh environments.
 - ◆ Maintenance free battery and external charger: easy for maintenance, better heat dissipation.
 - ◆ Optional: waterproof protection for electronic components.

参数项目Parameters / 型号Model		SL15	SL15Low (低放型)
额定载荷 Capacity	Kg	1500	1500
载荷中心 Load center	mm	600	600
转弯半径 Turning radius	mm	1440	1440
起升高度 Max. height	mm	200	180
货叉最低高度 Min. height	mm	85	65
货叉尺寸 Fork size	mm	150x1150	150x1150
货叉外宽 Fork width	mm	560/685	560/685
整车宽度 Overall width	mm	560/685	560/685
整车长度 Overall length	mm	1624	1624
整车高度 Overall height	mm	1174	1174
最大爬坡能力(满载/空载) Climbing ability(laden/ unladen)	%	5/15	5/15
驾驶方式 Driving Method		步行Walk	步行Walk
驱动电机 Drive motor		24V / 0.75KW	24V / 0.75KW
蓄電池 Battery		2x12V / 65 Ah	2x12V / 65 Ah
蓄電池充满电工作时间 Working hours once fully charged	h	3.5	3.5
自重 Weight	kg	150/190	145/185
电池重 Battery weight	kg	40	40
驱动轮 Driving wheel	mm	φ 210x70	φ 210x70
承载轮 Load wheel	mm	φ 80x60	φ 60x60

手动液压托盘搬运车 Hand Pallet Truck

- ◆ 专利“鳄鱼头”叉嘴：不易变形，便于保养维修。
- ◆ 专利防水油泵：不漏油，防尘防水，寿命长。
- ◆ 人字型峰部承顶盖：增强承托能力。
- ◆ 双泵双阀：耐用，延长油泵寿命。
- ◆ 喷粉涂层：颜色均匀耐用。
- ◆ 锻打杠杆架，高品质轴承和钢材：降低滚动阻力，转向更灵活，拖拉更轻盈。
- ◆ Patented "alligator fork head":not easy to deformation,easy maintenance.
- ◆ Patented waterproof oil pump:no leakage, durability that lasts.
- ◆ Herringbone top cover:enhanced support capablilty.
- ◆ Dual pump and dual valves:durability, extended oil pump life.
- ◆ Powder coating:quality paint and durable.
- ◆ Forged lever, high quality componenets and bearings:low rolling resistance, more flexible steering and excellent maneuverability.



◆ 新款手动液压托盘搬运车
New Style Hand Pallet Truck

参数项目Parameters/ 型号Model		CBYAK-N2.5	CBYAK-N3.0	CBYAK-N3.8
额定载荷 Capacity	Kg	2500	3000	3800
起升高度 Max.lift height	mm	175/185/195	185/195	195
货叉最低高度 Min.height	mm	65/75/85	75/85	85
货叉长度 Fork length	mm	1150/1220	1150/1220	1150/1120
货叉外宽 Fork width	mm	550/685	550/685	550/685
大轮直径 Diameter of the real wheel	mm	φ 180X50	φ 180X50	φ 180X50
前轮直径 Diameter of the front wheel	mm	φ80X70	φ80X70	φ80X70
转向 Turning degree		210°	210°	210°
自重 Weight	Kg	65-70	70-80	80-90

- ◆ 人字型峰部承顶盖：增强承托能力。
- ◆ 双泵双阀：耐用，延长油泵寿命。
- ◆ 喷粉涂层：颜色均匀耐用。
- ◆ 锻打杠杆架，高品质轴承和钢材：降低滚动阻力，转向更灵活，拖拉更轻盈。
- ◆ Herringbone top cover:enhanced support capablilty.
- ◆ Dual pump and dual valves:durability, extended oil pump life.
- ◆ Powder coating:quality paint and durable.
- ◆ Forged lever, high quality componenets and bearings:low rolling resistance, more flexible steering and excellent maneuverability.



◆ 经典款手动液压托盘搬运车
Classic Style Hand Pallet Truck

参数项目Parameters/ 型号Model		CBYAK2.0	CBYAK2.5	CBYAK3.0	CBYAK5.0
额定载荷 Capacity	Kg	2000	2500	3000	5000
起升高度 Max.lift height	mm	175/185/195	175/185/195	185/195	195
货叉最低高度 Min.height	mm	65/75/85	65/75/85	75/85	85
货叉长度 Fork length	mm	1150/1220	1150/1220	1150/1220	1150/1220
货叉外宽 Fork width	mm	550/685	550/685	550/685	550/685
大轮直径 Diameter of the real wheel	mm	φ 180X50	φ 180X50	φ 180X50	φ 180X50
前轮直径 Diameter of the front wheel	mm	φ80X70	φ80X70	φ80X70	φ80X70
转向 Turning degree		210°	210°	210°	210°
自重 Weight	Kg	62-67	65-70	75-82	160-170

全电动堆垛车 Electric stacker



- ◆高配置进口系统和无刷交流驱动电机：马力和稳定可靠。
 - ◆门架导轮，链轮和轴承都采用大叉车设计：提升工作效率，减少产品损坏。
 - ◆急停装置：提高操作人员安全性。
 - ◆多功能控制手柄：符合人体工学，提供操作舒适度。
 - ◆高质量的防护玻璃：能见度高，安全可靠。
 - ◆电子转向：反应灵敏，操控灵活。
 - ◆可选：机械转向，可调节前腿，吸震防滑站台。
- ◆Curtis control system and brushless AC drive motor: powerful, improved work efficiency, and reliability.
 - ◆Forklift mast wheel, sprocket, chain, and bearings: increased work efficiency, eliminating costly repair.
 - ◆Operation handle: ergonomics, comfortable operation, increased work efficiency, break override feature.
 - ◆High quality protective glass: exceptional visibility, ensures operator's safety.
 - ◆Electronic steering: experiences less fatigue, more accurate control.
 - ◆Optional: mechanical steering, adjustable baseleg or straddle, shock-absorbing platform.

参数项目Parameters / 型号Model		CL-10	CL-12	CL-15
额定载荷 Capacity	kg	1000	1200	1500
起升高度 Max. lift height	mm	1600/2600/3200/3600	1600/2600/3200/3600	1600/2600/3200/3600
货叉外宽 Overall fork width	mm	570/690	570/690	570/690
货叉尺寸 Fork length	mm	1150	1150	1150
货叉最低高度 Min. height	mm	86	86	86
整车高度 Overall height	mm	2000/1800/2100/2350	2000/1800/2100/2350	2000/1800/2100/2350
整车宽度 Overall width	mm	805	805	805
整车长度 Overall length	mm	1865	1865	1865
转弯半径 Turning radius	mm	1436	1436	1436
载荷中心 Load center	mm	600	600	600
蓄电池容量 Battery capacity	V/A	24V/210Ah	24V/210Ah	24V/210Ah
充电器 Charger		24V/30A	24V/30A	24V/30A
自重 Weight	Kg	817-927	827-937	827-937
电池重量 Battery weight	Kg	175	175	175